Application No.: 10/575,777 Docket No.: 0599-0215PUS1
Page 2 of 7

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A laminated film, comprising 5 or more laminated resin layers consisting essentially of resin layers of composition A and resin layers of composition B; the thickness of each of the resin layers being from 1 to 100 nm and the thickness of each of 75% or more layers constituting the laminated film being 30 nm or less; and the film having a layer structure wherein the thicknesses of resin layers having the same composition A increase or decrease from the side of a surface of the laminated film toward the side of the other surface opposite thereto and wherein the maximum light ray reflectivity for unpolarized light is 25% or less in a wavelength range of 400 to 2500 nm.

- 2. (Previously Presented) The laminated film according to claim 1, comprising the resin layers of the composition A, and resin layers having a composition B; and having a layer structure wherein the thickness ratio between the resin layer having the composition A and the resin layer having the composition B which are adjacent to each other increases or decreases from the side of the surface of the laminated film toward the side of the other surface opposite thereto.
- 3. (Previously Presented) The laminated film according to claim 1, comprising the resin layers of the composition A, and resin layers having a composition B; and having a layer structure wherein the thicknesses of the resin layers having the composition A increase from the side of the surface of the laminated film toward the side of the other surface opposite thereto, and thicknesses of the resin layers having the composition B decrease from the side of the surface of the laminated film toward the side of the other surface opposite thereto.
- 4. (Previously Presented) The laminated film according to claim 1, having a layer structure wherein the thicknesses of the resin layers having the composition A increase from the first surface towards the center and then decrease from the center to the other surface or decrease from the first surface toward the center and then increase from the center to the other surface.
- 5. (Cancelled)

Application No.: 10/575,777 Docket No.: 0599-0215PUS1
Page 3 of 7

6. (Cancelled)

7. (Previously Presented) The laminated film according to claim 1, comprising a pair of adjacent

resin layers wherein the ratio between the thicknesses of the adjacent layers (the thickness of the

thin layer to that of the thick layer) is 0.8 or more and 1.0 or less, and a pair of adjacent ones of

the resin layers wherein the ratio between the thicknesses of the adjacent layers is 0.01 or more

and 0.5 or less.

8. (Previously Presented) The laminated film according to claim 1, wherein the number of the

laminated layers is 50 or more.

9. (Cancelled)

10. (Previously Presented) The laminated film according to claim 2, comprising two

thermoplastic resins having a refractive index difference of 0.05 or more.

11. (Previously Presented) The laminated film according to claim 3, comprising two

thermoplastic resins having a refractive index difference of 0.05 or more.

12. (Previously Presented) The laminated film according to claim 4, comprising two

thermoplastic resins having a refractive index difference of 0.05 or more.

13.-15. (Cancelled)

16. (Previously Presented) The laminated film according to claim 2, comprising a pair of

adjacent resin layers wherein the ratio between the thicknesses of the adjacent layers (the

thickness of the thin layer to that of the thick layer) is 0.8 or more and 1.0 or less, and a pair of

adjacent ones of the resin layers wherein the ratio between the thicknesses of the adjacent layers

is 0.01 or more and 0.5 or less.

Application No.: 10/575,777 Docket No.: 0599-0215PUS1
Page 4 of 7

17. (Previously Presented) The laminated film according to claim 3, comprising a pair of adjacent resin layers wherein the ratio between the thicknesses of the adjacent layers (the thickness of the thin layer to that of the thick layer) is 0.8 or more and 1.0 or less, and a pair of adjacent ones of the resin layers wherein the ratio between the thicknesses of the adjacent layers is 0.01 or more and 0.5 or less.

18. (Previously Presented) The laminated film according to claim 4, comprising a pair of adjacent resin layers wherein the ratio between the thicknesses of the adjacent layers (the thickness of the thin layer to that of the thick layer) is 0.8 or more and 1.0 or less, and a pair of adjacent ones of the resin layers wherein the ratio between the thicknesses of the adjacent layers is 0.01 or more and 0.5 or less.

18. - 20. (Cancelled)